

United States Patent [19]

Randall

3,117,701

3,563,422

3,833,150

3,980,211

2/1971

9/1974

Patent Number: [11]

5,938,087

Date of Patent:

Aug. 17, 1999

[54]	SPURT MINIMIZING DISPENSING STRUCTURE				
[75]	Inventor: Jeffrey T. Randall, Oconomowoc, Wis.				
[73]	Assignee: AptarGroup, Inc., Crystal Lake, Ill.				
[21]	Appl. No.: 08/877,759				
[22]	Filed: Jun. 17, 1997				
[51]	Int. Cl. ⁶ B65D 47/40				
[52]	U.S. Cl				
[58]	Field of Search				
	222/568, 571				
[56]	References Cited				
U.S. PATENT DOCUMENTS					
3,091,373 5/1963 Kirschenbaum 222/547					

1/1964 Stull 222/571

9/1976 Owens 222/547

Cruikshank 222/547

Visser-Patings 222/571

4,583,668	4/1986	Maynard, Jr	222/568
4,811,871	3/1989	Wass et al	222/477
5,139,182	8/1992	Appla	222/547
5.141,138		Odet et al	
5,219,100	6/1993	Beck et al	222/556
5,320,260	6/1994	Song et al	222/547
5.392.938	2/1995	Dubach	215/254
5,454,489	10/1995	Vesborg	222/547
5,497,906		Dubach	
5.531,363		Gross et al	
5,782,388		De Nervo	
5,.02,500	., 2,,,0	-	

Primary Examiner-J. Casimer Jacyna

Attorney, Agent, or Firm-Rockey, Milnamow & Katz, Ltd.

ABSTRACT [57]

A spurt-resistant spout for a dispensing structure includes (1) an internal tubular portion having a through bore connecting a dispensing orifice of the spout with the interior of the container, and (2) a surrounding wall portion surrounding the tubular portion. The tubular portion and the surrounding wall portion are sized and located so that little or no fluid is retained in and across the spout bore so as to prevent, or minimize, obstruction of the bore.

26 Claims, 2 Drawing Sheets

